

<b>Model</b>	<b>TD-7451AS2</b>
<b>Camera</b>	
<b>Image Sensor</b>	<b>1 / 2.5 "CMOS</b>
<b>Resolution</b>	<b>5MP</b>
<b>Image Size</b>	<b>2560 x 1936</b>
<b>Video Output</b>	<b>AHD / TVI /CVI</b>
<b>Image System</b>	<b>PAL / NTSC</b>
<b>Electronic Shutter</b>	<b>Auto; 1/50s~1/000000s(P); 1/60s~1/100000s(N)</b>
<b>LED View Distance</b>	<b>20 ~30 m</b>
<b>Frame Rate</b>	<b>5MP@20fps/4MP@30fps</b>
<b>Min. Illumination</b>	<b>0 lux with LED ON</b>
<b>Lens</b>	<b>3.6 mm</b>
<b>Lens Mount</b>	<b>M12</b>
<b>S / N Ratio</b>	<b>≥52dB ( AGC OFF )</b>
<b>Ingress Protection</b>	<b>IP 67</b>
<b>Functions</b>	
<b>Function Control</b>	<b>OSD ( COC Control )</b>
<b>Smart LED</b>	<b>Yes</b>
<b>Digital WDR</b>	<b>Yes</b>
<b>Digital NR</b>	<b>Yes, 2D DNR</b>
<b>Global Exposure</b>	<b>Yes</b>
<b>Central Exposure</b>	<b>Yes</b>
<b>AGC</b>	<b>Yes</b>
<b>Auto White Balance</b>	<b>Yes</b>
<b>BLC</b>	<b>Yes</b>
<b>Front Light Compensation</b>	<b>No</b>
<b>Contrast</b>	<b>Yes</b>
<b>Sharpness</b>	<b>Yes</b>
<b>Image Setting</b>	<b>Yes</b>
<b>Defect Correction</b>	<b>Auto</b>
<b>Language</b>	<b>Chinese and English</b>
<b>Angle Adjustment</b>	<b>Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°</b>
<b>Others</b>	
<b>Power Supply</b>	<b>DC12V ( ± 10% )</b>
<b>Power Consumption</b>	<b>LED OFF : &lt; 1.5W; LED ON : &lt;3W</b>
<b>Working Environment</b>	<b>- 30 °C ~ 50 °C, 10 % ~ 90 % ( relative humidity )</b>

Dimensions ( mm )	165.7 x 69 x 69
Weight ( net )	Approx. 0.37KG