


## TD-9421S4-C

2MP Dual Illumination Water-proof  
Bullet Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution:2MP ( 1920 × 1080)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 20~30m white light view distance; 20~30m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support P2P function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23<sup>rd</sup> Floor, Block B4, Building NO.9, Shenzhen Bay  
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong  
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)


## SPECIFICATIONS

| Model                      | Specifications                                                                                                                                                                                    |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TD-9421S4-C                |                                                                                                                                                                                                   |
| Camera                     |                                                                                                                                                                                                   |
| Image Sensor               | 1 / 2.8 "CMOS                                                                                                                                                                                     |
| Image Size                 | 1920×1080                                                                                                                                                                                         |
| Electronic Shutter         | 1/3s ~ 1 / 100000s                                                                                                                                                                                |
| Iris Type                  | Fixed Iris                                                                                                                                                                                        |
| Min. Illumination          | 0.008 lux @F1.6, AGC ON; 0 lux with illumination on                                                                                                                                               |
| Lens                       | 2.8mm@F1.6, Horizontal FoV: 107°; Vertical FoV:56°;Diagonal FoV:126°<br>3.6mm@F1.6, Horizontal FoV:89°; Vertical FoV:47.5°;Diagonal FoV:104°                                                      |
| Focus                      | Fixed                                                                                                                                                                                             |
| Lens Mount                 | M12                                                                                                                                                                                               |
| Wide Dynamic Range         | 120dB                                                                                                                                                                                             |
| BLC                        | Yes                                                                                                                                                                                               |
| HLC                        | Yes                                                                                                                                                                                               |
| Digital NR                 | Yes                                                                                                                                                                                               |
| S/N Ratio                  | ≥50dB                                                                                                                                                                                             |
| Angle Adjustment           | Pan: 0°~360°; Tilt:0°~80°;Rotation: 0°~360°                                                                                                                                                       |
| Image                      |                                                                                                                                                                                                   |
| Video Compression          | Main stream: H.265+ / H.265 / H.264+ / H.264<br>Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG<br>Third stream: H.265+ / H.265 / H.264+ / H.264/ MJPEG                                       |
| H.265 Compression Standard | Main Profile@Leve4.1 High Tier                                                                                                                                                                    |
| Resolution                 | 1080P (1920×1080 ), 720P(1280×720), D1, VGA (640×480), 480× 240, CIF                                                                                                                              |
| Main Stream                | 1080P/720P (60Hz: 1~30fps; 50Hz: 1~25fps)                                                                                                                                                         |
| Sub Stream                 | D1/VGA/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)                                                                                                                                                         |
| Third Stream               | D1/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)                                                                                                                                                    |
| Bit Rate                   | 64 Kbps ~ 6 Mbps                                                                                                                                                                                  |
| Bit Rate Type              | VBR / CBR                                                                                                                                                                                         |
| Image Settings             | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser                                         |
| Audio Compression          | G711A/U                                                                                                                                                                                           |
| ROI                        | Each ROI to be configured separately                                                                                                                                                              |
| Interfaces                 |                                                                                                                                                                                                   |
| Network                    | RJ45                                                                                                                                                                                              |
| Video Output               | No                                                                                                                                                                                                |
| Audio                      | 1CH audio input; 1CH built-in MIC                                                                                                                                                                 |
| Storage                    | Built-in micro SD card slot, up to 256GB                                                                                                                                                          |
| Reset                      | Yes                                                                                                                                                                                               |
| Functions                  |                                                                                                                                                                                                   |
| Remote Monitoring          | Web browser /TVT NVR/NVMS2.X/Mobile APP                                                                                                                                                           |
| Web Browser                | Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+                                                                                                                                                |
| Online Connection          | Support simultaneous monitoring for up to 6 users;<br>Support multi-stream real time transmission                                                                                                 |
| Network Protocol           | UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS                                                                   |
| Interface Protocol         | ONVIF                                                                                                                                                                                             |
| Storage                    | Network remote storage; micro SD card storage                                                                                                                                                     |
| Smart Alarm                | Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, video exception                                                                                   |
| Smart Event                | Line crossing/region intrusion (human/vehicle classification), abandoned/missing object detection                                                                                                 |
| General Function           | Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern                                                                              |
| PoE                        | Yes (IEEE802.3af)                                                                                                                                                                                 |
| Supplement Light Range     | IR range: 20 ~ 30 m; white light range:20 ~ 30 m                                                                                                                                                  |
| Ingress Protection         | IP67                                                                                                                                                                                              |
| Security                   | Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP |

## DORI Distance

| Lens                     | Detect                                                                                       | Observe   | Recognize | Identify |
|--------------------------|----------------------------------------------------------------------------------------------|-----------|-----------|----------|
| 2.8mm                    | 41m(133ft)                                                                                   | 16m(53ft) | 8m(27ft)  | 4m(13ft) |
| 3.6mm                    | 50m(163ft)                                                                                   | 20m(65ft) | 10m(33ft) | 5m(16ft) |
| <b>Others</b>            |                                                                                              |           |           |          |
| Power Supply             | DC12V/PoE                                                                                    |           |           |          |
| Power Consumption        | < 6W                                                                                         |           |           |          |
| Storage Conditions       | - 30 °C ~ 65 °C (-22 °F~149 °F), Humidity: less than 95 % (non-condensing)                   |           |           |          |
| Operating Conditions     | - 30 °C ~ 60 °C (-22 °F~140 °F), Humidity: less than 95 % (non-condensing)                   |           |           |          |
| Dimensions ( mm )        | 167.6 × 75 × 74.6                                                                            |           |           |          |
| Weight ( net )           | Approx. 0.45KG                                                                               |           |           |          |
| Installation             | Ceiling mounting; wall mounting                                                              |           |           |          |
| Certificate              | CE, FCC                                                                                      |           |           |          |
| Environmental Protection | Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006) |           |           |          |

## DIMENSIONS



## AVAILABLE ACCESSORIES



## AVAILABLE MODEL

|                 |                       |
|-----------------|-----------------------|
| Available Model | TD-9421S4-C(D/PE/AW2) |
|-----------------|-----------------------|